

PH365L - AIR / WATER - LIGHT DUTY

Polyhose Proprietary Product



Construction

Core Plasticized PVC, Black

Reinforcement Single braid of Synthetic fiber

Cover Abrasion resistant thermo-compound, black Colour

Application Specially designed for Tyre inflation, light engineering industry and general purpose air line

Note: Special colours available on request

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH365L-04	-04	06	1/4	6.5	0.453	11.5	230	16	920	64	2.4	60	90.0
PH365L-05	-05	08	5/16	8.0	0.530	13.5	230	16	920	64	3.3	85	130.0
PH365L-06	-06	10	3/8	9.5	0.590	15.0	230	16	920	64	4.3	110	150.0
PH365L-08	-08	12	1/2	12.7	0.736	18.7	230	16	920	64	5.1	130	220.0
PH365L-12	-12	19	3/4	19.0	1.024	26.0	145	10	580	40	5.7	145	330.0
PH365L-16	-16	25	1	25.4	1.240	31.5	145	10	580	40	6.7	170	450.0



Temperature Range: Continuous: -10°C to +60°C